



Datasheet – Junior Bau

Technical Data

Speed	24 – 48 m/min
Payload	250 kg
Drive	Hydraulic power unit 2,6kW, 230V
Load winch	hydraulic
Rotary unit	Kingpin with Slide bearings
Cable length	55,000 mm
Accessories	mechanical remote control
Options	Gasoline engine, retractable axle, attachable knee joint

Description	Junior 18 / 0-5 without brake	Junior 18 / 0-5	Junior 21 / 0-6	Junior 24 / 0-7	Junior 24K / 0-7
Dead weight (kg)	750	1200	1200	1200	1200
Dimensions (W x L)	1270 x 4890	1270 x 4900	1270 x 4900	1270 x 4900	1270 x 5200
Lifting height	4000 x 17,850	4000 x 17,850	4100 x 20,900	4110 x 23,670	4100 x 23,800
Rail package length (mm)	4005	4005	4060	4115	4072
Rail quantity (W sections)	6	6	7	8	8
Gauge (mm)	540	540	540	540	540
Supports (mm)	1x center, fixed, front, 2x plug-in, back	4 plug-in, Support surface 2300 x 2800	4 plug-in, Support surface 2300 x 2800	4 plug-in, Support surface 2300 x 2800	4 plug-in, Support surface 2300 x 2800
Drawbar	retractable and adjustable Ball coupling	straight, retractable and adjustable	straight, retractable and adjustable	straight, retractable and adjustable	straight, retractable and adjustable